



SVELT EURO C3 5W-30

[Product Introduction]

New "SVELT EURO" series got the approval from the latest standard API:SP and ACEA:C3 and compatible with European gasoline and diesel engine vehicles equipped GPF and DPF. SVELT EURO C3 5W-30 satisfies requirements for the latest engine oil at high levels such as engine protection, performance for exhaust gas after-treatment devices and long-life performance. The most suitable engine oil to keep the best performance of a vehicle long.

[Product Features]

- High-performance oil that has acquired both ACEA and API standards.
- Overwhelming lubrication performance with "ES-COMBINATION" (ester-formulation).

[International Standards/OEM Approvals]

API:SP, ACEA:C3, MB-Approval 229.51

[OEM Performances]

MB 229.31, MB 229.52, BMW LL-04, VW 504/507, Porsche C30, OPEL ov0401547

[Meet]

API CF-4

[Recommendation]

- For European cars with GPF or DPF.
- For European car owners who want to combine oil evaporation, engine protection, and fuel economy.
- For Japanese car owners cars who value engine protection performance.
- For car owners who occasionally drive on circuits without special tuning.





PRODUCT INFORMATION

SUNOCO MAKES THE DIFFERENCE

[Applicable Engines / Car Models]

- Gasoline Engines / Diesel Engines
 - European Cars (Mercedes-Benz, BMW, VW, Audi, etc.)
 - Japanese Cars (TOYOTA, Nissan, Honda, etc.)
 - Mercedes-Benz : CLS, GLS, GLE, etc.
 - BMW : 218d, 320d, etc.
 - VW : GOLF, POLO, Touran, Tiguan, Passat Variant, etc.
- ※Please note that compatibility may vary depending on the vehicle and engine model.

[Typical]

Base Oil Type	Full Synthetic
Density (15°C g/cm ³)	0.8537
Flash Point (°C)	224
Pour Point (°C)	-35.0
Kin. Vis. (40°C mm ² /s)	68.52
Kin. Vis. (100°C mm ² /s)	11.92
Viscosity Index	172
HTHS (150°C mPa.s)	3.5

[Packaging]

200L Drum, 20L Pail, Carton Case (4Lx4), Carton Case (1Lx10)

[Cautions]

- Please confirm the recommended viscosity and specifications in the car manual.