



## ***SVELT EURO 5W-50***

### **[Product Introduction]**

New “SVELT EURO” series got the approval from the latest standard API:SP and ACEA:A3/B4 and compatible with European gasoline and diesel engine vehicles.

SVELT EURO 5W-50 covers in a wide range and protects an engine with thicker oil film even short time and distance driving. This oil is suitable to keep performance of overrun and/or aged vehicles also.

### **[Product Features]**

- High-performance oil that has acquired both ACEA and API standards.
- Overwhelming lubrication performance with “ES-COMBINATION” (ester-formulation).

### **[International Standards/OEM Approvals]**

API:SP, ACEA:A3/B4

### **[OEM Performances]**

MB 226.5, MB 229.3, MB 229.5, BMW LL-01, VW 502/505,  
Porsche A40, Renault RN0700, RN0710

### **[Meet]**

API CF-4

### **[Recommendation]**

- For European car owners and Japanese car owners who want to focus on engine protection performance.
- For owners who want to take good care of their overrun and/or aged vehicles.





## PRODUCT INFORMATION

### [Applicable Engines / Car Models]

- Gasoline Engines / Diesel Engines
  - European Cars (Mercedes-Benz, BMW, VW, Audi, etc.)
  - Japanese Cars (TOYOTA, Nissan, Honda, etc.)
  - Mercedes-Benz : A-class, C-class, GLA, S-class, etc.
  - BMW : 3 series, X series, etc.
- ※Please note that compatibility may vary depending on the vehicle and engine model.

### [Typical]

Base Oil Type	Full Synthetic
Density (15°C g/cm <sup>3</sup> )	0.8569
Flash Point (°C)	234
Pour Point (°C)	-45.0
Kin. Vis. (40°C mm <sup>2</sup> /s)	118.7
Kin. Vis. (100°C mm <sup>2</sup> /s)	19.10
Viscosity Index	182
HTHS (150°C mPa.s)	4.2

### [Packaging]

200L Drum, 20L Pail, Carton Case (4Lx4), Carton Case (1Lx10)

### [Cautions]

- Please confirm the recommended viscosity and specifications in the car manual.
- We do not recommend to apply this oil for the vehicles that recommend lower viscosity oils (such as 0W-16, 0W-20).