



MARVIC ATF

(Marvic ATF)

Product Description

This is a mineral oil-based ATF that meets the standards of DEXRON II, III, IIIH, MERCON V, etc., which are compatible with foreign (non-Japanese) cars from the 1980s to 2000s. This ATF is ideal for those who want to enjoy the unique feel of mineral oil.

Features

- Compatible with wet clutches

The friction characteristics of ATF are optimized to prevent vibrations and shock when engaging the clutch, achieving a smooth feel.

- Shudder performance compatible with every OEM oil

Achieves long AT life by meeting the shudder resistance required by every OEM oil.

- Excellent compatibility with seal materials

This oil has been tested for compatibility with seal materials used by various manufacturers and has met their required standards. As a result of extensive testing, this oil is ideal for preventing oil loss.

- Compatible with DEXRON and MERCON standards

Compatibility with DEXRON II, III, IIIH and MERCON V makes it the ideal oil for foreign (non-Japanese) cars from around the 1980s to the 2000s.



Recommendations

- Vehicles that specify DEXRON II, III, IIIH, and MERCON V
- Foreign (non-Japanese) cars from around the 1980s to the 2000s

■ MARVIC ATF
■ Mineral oil
■ Equivalent standard: MERCON® V DEXRON® II, III, IIIH

Usage Precautions

- In cars that have run over 50,000 km without replacing the ATF, and cars with high mileage of over 100,000 km, or vehicles already experiencing slippage or other abnormalities, mechanical problems due to internal AT wear, etc. may exist.

Be sure to check the vehicle's condition before carrying out the work.

- Be sure to check ATF compatibility before use.



Typical Properties

Density (15°C g/cm ³)	0.8508
Flash point (°C)	208
Pour point (°C)	-47.5
Kinematic viscosity (40°C mm ² /s)	37.50
Kinematic viscosity (100°C mm ² /s)	7.745
Viscosity index	183
Hue	Red

Product Packaging and JAN Code

- Package 20L JAN4531291008506
200L drum